

Model T30



The FINN T30 HydroSeeder has been modified and redesigned to provide the ideal entry-level machine loaded with features that come standard with every unit. The T30 is the perfect FINN HydroSeeder for tackling smaller hydroseeding projects or an affordable way of adding to an existing fleet.

FINN developed HydroSeeder technology in 1953 and we've been the industry leader in quality and innovation ever since. With the FINN T30, you don't have to settle for less than proven and reliable FINN quality for a wide array of the most common hydroseeding applications.

Versatile & Economical.

The T30 is FINN's most economical HydroSeeder ever. You can easily manage professional quality seeding, fiber mulching, straw tacking, and much more - all with legendary FINN efficiency and cost effectiveness.

Feature-Packed Machine.

The FINN T30 HydroSeeder features a durable, 335 gallon liquid capacity steel tank; a hydraulically-driven and

reversible mechanical agitator for fast and thorough mixing; simple controls for economical one-man operation; a FINN-designed centrifugal pump that handles the thickest of slurries with ease; and forklift channels and lift ring for easy handling.

All T30 machines come standard with a powerful electric hose reel equipped with 100 feet of hose.

All Around Performance.

The T30 goes everywhere you need it to go: residences, cemeteries, golf courses, sports fields, office and apartment complexes, parks, and more.


As the world leader for over 80 years in the design and manufacture of innovative, quality equipment for the green industry, and as the inventor of the HydroSeeder, FINN Corporation is committed to your complete satisfaction.






Model T30

T30 HYDROSEEDER®





FINN MODEL T30 TECHNICAL SPECIFICATIONS

POWER	Kohler CH620 19 hp (14.2 kw), electric start,
	air cooled gas, oil guard protection

LOADS PER ACRE*..... 10.68

FUEL TANK4 gallon (15.1 liter)

CAPACITY

PUMP..... Centrifugal 3" x 1 1/2" (7.5 cm x 3.75 cm), 65 GPM @ 60 psi (227 lpm @ 414 kPa),

3/4" (1.9 cm) solid clearance

PUMP DRIVE...... Direct drive through electric clutch,

pump drive is independent of agitator operation

AGITATION.....Mechanical paddle agitation and liquid recirculation

AGITATOR DRIVE......Reversible, variable speed hydraulic motor

(0-130 rpm)

DISCHARGEUp to 70 ft. (23 m) from end of hose

DISTANCE

MATERIAL 500 lbs. (227 kg) granular solids,

CAPACITY 100 lbs. (45 kg) fiber mulch

NOZZLES.....(1) narrow fan, (1) wide fan, (1) long distance

HOSE REELStandard electric hose reel with a 12V electric motor,

100' x 1 1/4" semi-rigid polybraid hose and hose holder

EMPTY WEIGHT1,480 lbs. (671 kg)

WORKING WEIGHT*..... 4,560 lbs. (2,068 kg)

*Loads per acre based on an application rate of 1500 lbs. mulch/acre.

*Working weights are approximate and do not include stored materials.

FINN Corporation has a policy of continuous product improvement, and reserves the right to change design and specifications without notice.

HydroSeeder® and the FINN Design® Logo are registered trademarks of FINN Corporation.